






Energy Storage System (ESS) for residential applications -

STORION SERIES SMILE-B3




✓ Key Features

-  **AC-Coupling**
-  **Built-in battery**
-  **Modular design**
-  **Easy installation and low maintenance**
-  **24/7 Monitoring**



Real-time Monitoring

All systems can be monitored by **Web and iOS/Android APP**.



Safest Chemistry

AlphaESS uses Li-phosphate for its excellent safety and long lifespan.

About AlphaESS

As one of the earliest pioneers in energy storage market with lithium iron technology, AlphaESS has a vision to pave the path for everyone in the world to enjoy clean energy one day.

AlphaESS is a multinational company that currently has more than 10'000 residential and commercial systems running in 30 countries globally and its products are accredited by IEC, TÜV, CEC and many other international standards.

All AlphaESS energy systems are integrated with smart energy management solutions. AlphaESS is committed to revolutionize the future energy network through our patented German technologies.



Official Website



Scan to download APP (iOS/Android)



Twitter



FaceBook

System Specification	
Model	Storion-SMILE-B3
Max. AC Output Power	3000 W
Max. AC Input Power	3000 W
IP Protection	IP65
Dimension (W x D x H)	610 mm x 236 mm x 625 mm
Weight	45 kg
Operating Temperature Range	-10 °C ~ 50 °C *
Warranty	5 Year Product Warranty, 10 Year Performance Warranty

Inverter Technical Specification	
Max. AC Input Current	13 A
Nominal AC Input Voltage	230 V
Battery Voltage Range	40 V ~ 58 V
Max. Charge/Discharge Current	60 A
Max. Charge/Discharge Power	3000 W
Phase	Single-Phase
Nominal AC Output Voltage	230 V
Grid Voltage Range	180 V ~ 270 V
Rated Frequency	50/60 Hz
Backup	UPS
Grid Regulation	AS 4777.2, VDE-AR-N 4105, G83/2
Safety	IEC 62040-1, IEC 62477-1

Battery Technical Specification	
Module Capacity	2.9 kWh (90% DoD)
Module Nominal Voltage	51.2 V
Cycle Life	≥ 6000
Max. Charge/Discharge Current	56 A (1C)
External Battery Expansion	1 ~ 5 M4856-P in parallel

*When the temperature is below 0 °C or above 40 °C, the performance will be limited.



Solar Group Limited

19 Arrenway Drive, Albany
PO Box 35588, Browns Bay
Auckland

P 09 477 2999

W solargroup.co.nz E info@solargroup.co.nz



Headquarter: Alpha ESS Co., Ltd.

☎ +86 (0) 513 806 068 91

✉ info@alpha-ess.com

🌐 www.alpha-ess.com

📍 JiuHua Road 888, Nantong High-Tech Industrial Development Zone, Nantong City, 226300

Germany: Alpha ESS Europe GmbH

☎ +49 (0) 6103 / 459 160-1

✉ europe@alpha-ess.de

🌐 www.alpha-ess.de

📍 Paul-Ehrlich-Straße 1a, 63225 Langen, Hessen

Australia: Alpha ESS Australia Pty. Ltd.

☎ +61 (0) 402 500 520 (Sales)

+61 1300 968 933 (Technical Support)

✉ australia@alpha-ess.com

🌐 www.alpha-ess.com.au

📍 Suite 2, Level 1, 530 Botany Road, Alexandria, NSW, 2015

Italy: Alpha ESS Italy S.r.l.

☎ +39 (0) 599 239 50

✉ info@alpha-ess.it

🌐 www.alpha-ess.it

📍 Via Loda, 17-41013 Castelfranco Emilia(MO)